CAD Tools for Creating 3D Escher Tiles

Mark Howison


Graphics Lunch, UC Berkeley February 26, 2009

Overview

- ▶ 2½D Tilings
- Incremental Delaunay Triangulation in Java
- Mesh-Cutting Algorithm
- Visual Debugging
- ▶ 3D Tilings
- User Interface Issues


Introduction

- M.C. Escher popularized intricately decorated isohedral tilings
- Planar tilings can be designed by hand, or with available tools on the web
- Specialized CAD tools help address the challenges of tiling other 2-manifolds
- What are interesting tilings of 3-space?



Tiling on 2-manifolds

In the plane





On the sphere

In the Poincaré disk





On a genus-3 "Tetrus" surface

2½D Tilings


- Warm-up exercise before tackling full 3D
- Extruded 2D tilings form layers in 3-space
 - Trivial case: extrude vertically, edit height field







Fancier case: choose an "offset" between adjacent layers










Triangulation Library

- Need meshes for boundary representation of tiles
- Why implement another triangulation library?
 - Chose Java for ease of UI development and portability
 - Could not find existing libraries native to Java
 - Using Triangle would require JNI or dumping/reading ASCII
 - Precise results are unnecessary
 - Limited by precision of Fused Deposition Machine
 - Don't need optimizations for large meshes, but do need support for frequent modifications
 - Opportunity to learn about data structures and algorithms for triangulation


Delaunay Triangulation

- The circumcircle through any triangle does not contain any other vertices of the triangulation
- "Locally equiangular": maximizes the minimum of the six angles within any two adjacent triangles
- Can use an *in-circle* test to determine if a triangulation is Delaunay
- Can make a triangulation Delaunay by flipping edges



Robustness

- Need reliable tests for determining if a vertex is:
 - Left/right of a line (orient)
 - Inside/outside the circumcircle of a face (in-circle)
- Exact arithmetic or adaptive precision arithmetic
 - Slow (exact) or complicated implementation (adaptive precision)
 - Precision is not crucial for our application
- Snap to integer coordinates, use integer arithmetic
 - Rotating/skewing/scaling the tile and computing intersections is awkward
 - Modern processors are designed for flops
- Merge vertices that lie within an epsilon radius
 - Use an epsilon >> floating point round-off error
 - Can still have problems with vertices within < epsilon of edges
 - Robust enough for our purposes ("quasi-robust" in Shewchuk's categorization)



Three Basic Types of Algorithms

- Divide-and-conquer (e.g., Shamos and Hoey)
 - Typically used to generate the Voronoi diagram
 - Can be modified to return the Delaunay triangulation, the dual of the Voronoi diagram
- Sweepline (e.g., Fortune)
 - Moving "front" along an axis guarantees that circumcircles behind the front can't contain new vertices
- Incremental insertion (e.g., Lawson)
 - Performance is limited by how well you can locate which triangle contains the insertion site
 - Many optimizations are available

Lawson's Incremental Insertion Algorithm

Nice properties

- Maintains the integrity of the mesh after every vertex insertion
- Easy to implement

Basic idea


- Locate triangle containing insertion site
- Trisect the triangle; add all involved edges to a queue
- Perform in-circle test on queue
 - If an edge fails the test, flip it and add its four neighbor edges back onto the queue
 - Guaranteed to terminate: can show that circumradii are strictly decreasing and there are only finitely many triangulations (Sibson)

Issues

- Locating insertion sites is the bottle-neck
- How do you insert a site outside of the boundary?


Locating Insertion Sites


- Easy if you have a convex boundary: walk along the triangles
- For non-convex boundaries, we load on-demand copies of the neighboring tiles to fill concavities
- Heuristic:
 use the last inserted
 site as the search
 origin, since a designer
 will often add vertices
 in localized groups




Moving/Removing Interior Vertices

- Temporary holes arise: need polygon filling algorithm
- We use a naïve $O(n^2)$ algorithm for ease of implementation
 - Recursively cuts off "ear" triangles
 - > Small polygons, mostly convex: performance isn't an issue
 - If performance were an issue, could use a smarter "trapezoidal decomposition" algorithm









Moving/Removing Boundary Vertices

- Case 1: Move vertex along the boundary
 - Assign new vertex coordinates
- Case 2: Move vertex into the exterior
 - 1. Assign new vertex coordinates
 - 2. Remove attached non-boundary edges
 - 3. Fill polygon left by removal




Moving/Removing Boundary Vertices (Cont'd)

- Case 3: Move vertex into the interior
 - 1. Assign new vertex coordinates
 - 2. Remove ...
 - a) attached non-boundary edges
 - b) edges that intersect adjacent boundary edges
 - c) any exterior edges and points
 - Fill polygon left by removal



Mesh-Cutting Algorithm


- ▶ For forming the bottom face of an offset 2½D tile
- Given an underlying mesh and a "cookie-cutter" template
- Truncates the geometry of the underlying mesh to fit inside






Mesh-Cutting Algorithm (Cont'd)

- 1. Template offset is specified by user
- Construct template as an empty boundary "shell" with temporary edges
 - Follow the template to identify intersections with the underlying mesh
 - Load underlying mesh copies ondemand
 - Add fragments that lie inside the template to a queue; check future intersections against the fragment queue



1.


2.



Mesh-Cutting Algorithm (Cont'd)


3. After finding all intersections, add fragments as constraint edges to the template shell

3.



4. Perform a flood search to capture the remaining geometry inside the template

4.




Visual Debugging

- Sophisticated algorithms are difficult to debug using traditional text-based debuggers/methods
- Geometric/graphics algorithms offer the advantage of visual debugging options
 - Animation and visualization help identify extreme, difficult, or unexpected cases
 - Can isolate and visualize subtasks within the algorithm
- Implemented in Java2D by overriding the event-queue repainting mechanism
 - Events can be inserted mid-algorithm to create visual "breakpoints"
 - Events can specify which geometric features to highlight

3D Tilings

Exploring two fundamental domains:

▶ #1: Truncated octahedron, derived from the body-centered




3D Tilings

Exploring two fundamental domains:

#2: Rhombic dodecahedron, based on the densest sphere

packing




Overview of 3D Editing Interface

Phase I:

- Individual "panes" of the 3D tile can be Delaunay triangulated
- Vertices can be moved in 2D within pane interior
- Boundary vertices cannot be moved yet, since this would create nonplanar panes


Phase II:

- All vertices can be moved in 3D:
 - Last selected point defines an axis through the origin
 - Can move points parallel to axis or in perpendicular plane
- Local edits available by trisecting faces, but no Delaunay guarantee
- Limited "roll-back" to Phase I




User Interface Issues

- Occlusion is an obstacle to free-form editing of 3D tiles
 - Because of symmetry, edits in the current view will also change opposite faces
 - Creating a convex feature (e.g. a fish fin) creates a corresponding concave feature (e.g. eye socket) on the opposite side
 - Dual cameras can show convex/concave pairings




User Interface Issues (Cont'd)

- ▶ 3D domains can be scaled/skewed and remain space-filling
- What is the easiest way to manipulate this affine transform?
 - Created a widget with 9 control points, each restricted to one degree of freedom
 - Widget maintains same orientation as camera



User Interface Issues (Cont'd)

- ▶ 3D tilings can have complicated interlocking features
- Nearest neighbors can be scaled/translated to reveal the interface between adjoining tiles



Conclusion

- ▶ Developed a CAD tool for designing layered 2½D tiles
 - Can draw on an existing "vocabulary" of 2D tilings from Escher's sketchbook
- ▶ 3D cubic lattice tiles are more difficult to design
 - The entire editable surface is constrained to fit seamlessly with adjacent tiles
 - In the 2D case, only the 1D border is subject to symmetry constraints, while the interior can be decorated freely
 - There is no Escher sketchbook for 3D
- Addressed several UI issues in our prototype 3D tool
 - Two-stage editing allows for Delaunay triangulation
 - Dual cameras reveal occluded features
 - Widget for controlling skew enables high-level editing operations
 - Interactive display of nearest neighbors shows how tiles interlock
- Will address future UI issues as we try to create attractive 3D tiles!